


Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Page 1/10




Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Rostumwandler



#### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 115-10-6	dimethyl ether	25-<50%
EINECS: 204-065-8	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
Reg.nr.: 01-2119472128-37-xxxx		
	(Cor	td. on page 3)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Rostumwandler

CAS: 67-64-1	acetone	ntd. of page 25-<50%
	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3,	20 (00)
	propan-2-ol	5-<10%
	butanone ✤ Flam. Liq. 2, H225; � Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%
	1-methoxy-2-propanol	2.5-<59
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<59
	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	1-<2.5%
	n-butyl acetate 🚸 Flam. Liq. 3, H226; 아 STOT SE 3, H336, EUH066	1-<2.5%
	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight 700-1100 $\bigcirc$ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ %	1-<2.59

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 3)

Trade name: Aerosol Rostumwandler

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

×

- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· 8.1 C	ontrol parameters	
· Ingre	dients with limit values that require monitoring at the workplace:	
115-1	0-6 dimethyl ether	
WEL	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm	
67-64	-1 acetone	
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm	
67-63	-0 propan-2-ol	
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm	
78-93	2-3 butanone	
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV	
		(Contd. on page 5) G

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 4)

Trade name: Aerosol Rostumwandler

1330-20-7 xylene, mixture of isomersWELShort-term value: 441 mg/m³, 100 ppm<br/>Long-term value: 220 mg/m³, 50 ppm<br/>Sk; BMGV108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

**123-86-4 n-butyl acetate** WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm

Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

### · Ingredients with biological limit values:

78-93-3 butanone BMGV 70 μmol/L

Medium: urine Sampling time: post shift Parameter: butan-2-one

### 1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- $\cdot$  General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- · Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

#### • Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

<sup>-</sup> GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Rostumwandler

- (Contd. of page 5) • For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm • Eye/face protection
- Safety glasses

· Lower:

· Upper:

 $\cdot pH$ 

· Flash point:

· Viscosity:

· Dynamic:

• Solubility • water:

· Ignition temperature:

· Kinematic viscosity

· Relative density

· Vapour density

· Solids content:

· Decomposition temperature:

• Vapour pressure at 20 °C:

· Density and/or relative density

· Partition coefficient n-octanol/water (log value)

Tightly sealed goggles

#### **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Physical state Aerosol · Colour: According to product specification · Odour: Characteristic Not determined. · Odour threshold: • Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling -24.9 °C range · Flammability *Not applicable.* · Lower and upper explosion limit

2.6 Vol % (67-64-1 acetone) 18.6 Vol % (115-10-6 dimethyl ether) <0 °C 235 °C (115-10-6 dimethyl ether) Not determined. Not determined.

Not determined. Not determined.

Not miscible or difficult to mix. Not determined. 3,400 hPa (115-10-6 dimethyl ether)

Not determined. Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of	f health and
environment, and on safety.	
• Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
	Not determined.
· Solvent content:	
· Organic solvents:	95.5 %
-	With propellant gas. Content given by weight.
$\cdot$ VOC (EU)	95.50 %

3.3 %

- (Contd. on page 7)
  - GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Rostumwandler

	(Contd. of page
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard	classes
• Explosives	Void
Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- $\cdot$  11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Rostumwandler

(Contd. of page 7)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Ikke relevant.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

\*

2

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

1950 0 AEROSOLS ROSOLS, flammable F Gases.
ROSOLS ROSOLS, flammable
F Gases.
F Gases.
F Gases.
Gases.
d classified
ning: Gases.
classified
,

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Rostumwandler (Contd. of page 8) F-D, S-U· EMS Number: SW1 Protected from sources of heat. · Stowage Code SW2 Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO Not applicable. instruments • Transport/Additional information: · ADR  $\cdot$  Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 · Tunnel restriction code D · IMDG  $\cdot$  Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

UN 1950 AEROSOLS, 2.1


· Directive 2012/18/EU

· UN "Model Regulation":

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Technical instructions (air):



· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

Extremely flammable gas. H220

(Contd. on page 10)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Rostumwandler

	(Control of more 0)
H225	(Contd. of page 9) Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	
	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
	8 In use may form flammable/explosive vapour-air mixture.
	6 Repeated exposure may cause skin dryness or cracking.
	5 Contains epoxy constituents. May produce an allergic reaction.
201120	Contains epoxy constructions. May produce an anergie reaction.
Depart	ment issuing SDS: Product safety department
Abbrev	iations and acronyms:
ADR: Ad	cord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the
	onal Carriage of Dangerous Goods by Road)
	nternational Maritime Code for Dangerous Goods
	ernational Air Transport Association
	obally Harmonised System of Classification and Labelling of Chemicals European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances
	emical Abstracts Service (division of the American Chemical Society)
	sistent, Bioaccumulative and Toxic
vPvB: ve	ry Persistent and very Bioaccumulative
	IS IA: Flammable gases – Category IA
	: Aerosols – Category 1
	s - Category 3
	is (Comp.): Gases under pressure – Compressed gas
	7. 2: Flammable liquids – Category 2 7. 3: Flammable liquids – Category 3
	x. 4: Acute toxicity – Category 4
	2: Skin corrosion/irritation – Category 2
	2: Serious eye damage/eye irritation – Category 2
	s. 1: Skin sensitisation – Category 1
	3: Specific target organ toxicity (single exposure) – Category 3
	2: Specific target organ toxicity (repeated exposure) – Category 2
	1: Aspiration hazard – Category 1
	compared to the previous version altered.