


Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Page 1/9



Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt

	(Contd. of page 1)
• Signal word Dar	nger
• Hazard statemer	nts
H222 Extremely	flammable aerosol.
H229 Pressurise	d container: May burst if heated.
H319 Causes ser	rious eye irritation.
· Precautionary st	tatements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
· Additional infor	mation:
Without adequat	e ventilation, explosive atmosphere/gas mix may be created.
Warning! Hazar	dous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH208 Contain	ns 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.
· 2.3 Other hazard	ds
· Results of PBT d	and vPvB assessment
· PBT: Not applic	able.
• vPvB: Not applie	cable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 115-10-6	dimethyl ether	25-<50%
EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
CAS: 64-17-5	ethanol	10-<25%
EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319	
CAS: 111-76-2	2-butoxyethanol	2.5-<5%
EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-xxxx	♦ Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	
CAS: 126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	≥0.1-<1%
EINECS: 204-809-1 Reg.nr.: 01-2119954390-39-XXXX	Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	
Additional information, For the w	ording of the listed hazard phrases refer to section 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt

(Contd. of page 2)

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

- WEL Short-term value: 958 mg/m³, 500 ppm
- Long-term value: 766 mg/m³, 400 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

(Contd. on page 4)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt (Contd. of page 3) · Ingredients with biological limit values: 111-76-2 2-butoxyethanol BMGV 240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Appropriate engineering controls No further data; see item 7. · Individual protection measures, such as personal protective equipment · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin. · Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply. · Hand protection Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves Nitrile rubber, NBR · Penetration time of glove material Gloves must be changed after every contamination. The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: butyl rubber, 0,7mm · Eye/face protection Safety glasses Tightly sealed goggles **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Physical state

- · Colour:

Aerosol According to product specification

(Contd. on page 5)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt

	(Contd. of page
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	-24.9 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	3 Vol % (115-10-6 dimethyl ether)
Upper:	18.6 Vol % (115-10-6 dimethyl ether)
Flash point:	<0 °C
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
pH -	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3,400 hPa (115-10-6 dimethyl ether)
Density and/or relative density	-, in a (110-10-0 annone); enter)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and	d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	66.9 %
Organic solvents:	With propellant gas. Content given by weight.
Organic solvents: Water:	
	With propellant gas. Content given by weight.
Water:	<i>With propellant gas. Content given by weight. 17.0 %</i>
Water: VOC (EU)	With propellant gas. Content given by weight. 17.0 % 66.93 %
Water: VOC (EU) Solids content: Change in condition	With propellant gas. Content given by weight. 17.0 % 66.93 %
Water: VOC (EU) Solids content: Change in condition Evaporation rate	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable.
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable.
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Void
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Void Extremely flammable aerosol. Pressurised container
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Void Extremely flammable aerosol. Pressurised container May burst if heated.
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Extremely flammable aerosol. Pressurised container May burst if heated. Void
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void Void Void
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Extremely flammable aerosol. Pressurised container May burst if heated. Void Void Void Void Void Void Void Void Void Void Void Void Void Void
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Extremely flammable aerosol. Pressurised container May burst if heated. Void
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Extremely flammable aerosol. Pressurised container May burst if heated. Void
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable.
Water: VOC (EU) Solids content: Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols	With propellant gas. Content given by weight. 17.0 % 66.93 % 0.1 % Not applicable. S Void Extremely flammable aerosol. Pressurised container May burst if heated. Void

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt

		(Contd. of page 5)
· Substances and mixtures, which emit fl	ammable	
gases in contact with water	Void	
• Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 37,687 mg/kg (ATE)

Inhalative LC50/4 h 94.2 mg/l (rat)

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
		400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (rat)

· Serious eye damage/irritation Causes serious eye irritation.

- \cdot 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- $\cdot \ \textbf{12.3 Bioaccumulative potential} \ \textit{No further relevant information available}.$
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)

GB -

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt

(Contd. of page 6)

· 12.7 Other adverse effects

 \cdot Additional ecological information:

· General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

2

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

14.1 UN number or ID number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
,	not classified
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
	not classified
EMS Number:	F- D , S - U
Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre:

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt

	(Contd. of page
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
· 14.7 Maritime transport in bulk accord	ling to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities ($\widetilde{E}Q$)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
\cdot Limited quantities (LQ)	1L
$\cdot Excepted$ quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

• Technical instructions (air):

Class	Share in %
Wasser	10-<25
NK	50-100

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

(Contd. on page 9)

⁻ GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol BT Spec Eisblumen Effekt

	(Contd. of page 8)
H318 Causes serious eye damage.	
H319 Causes serious eye irritation.	
H331 Toxic if inhaled.	
H412 Harmful to aquatic life with long lasting effects.	
EUH018 In use may form flammable/explosive vapour-air mixture.	
· Department issuing SDS: Product safety department	
· Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (Europed	an Aaraamant Concerning the
International Carriage of Dangerous Goods by Road)	an Agreement concerning the
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
: Aerosols – Category 3	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Lig. 2: Flammable liquids – Category 2	
Acute Tox. 4: Acute toxicity – Category 4	
Acute Tox. 3: Acute toxicity – Category 3	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1B: Skin sensitisation – Category 1B	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
• * Data compared to the previous version altered.	
	GB