

*

2

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Page 1/10

· 1.1 Product identij	logification of the substance/minture and	
· 1.1 Product identij	ieniijicailon of the substance/mixture and	d of the company/undertaking
	fier	
• Irade name: <u>Aero</u>	sol 1K Unifill S6 dunkelgrau	
1.2 Relevant ident	product ID.: REZ1310 ified uses of the substance or mixture and uses ad 1 Consumer uses: Private households / general pu	
	substance / the mixture: painting nst No further relevant information available.	
• 1.3 Details of the s • Manufacturer/Sup Peter Kwasny Gml Heilbronner Str. 9 D-74831 Gundelsk	БН 6	Tel.: 0049-(0)6269-95-20
		E-mail: labor@kwasny.de
· Further information	on obtainable from: Product safety department	
National Poisons I Tel.: 844 892 0111 • K-Nr. 0001	nformation Service, Birmingham	
SECTION 2: H	lazards identification	
	of the substance or mixture	
· Classification acco	ording to Regulation (EC) No 1272/2008	
🖌 💦 🔪 flame		
flame		
Aerosol 1	H222 Extremely flammable aerosol.	
	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.	
Aerosol 1	H229 Pressurised container: May burst if heated.	
Aerosol 1 Eye Irrit. 2	H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation.	
Aerosol 1 Eye Irrit. 2 Skin Sens. 1 STOT SE 3	H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.	
Aerosol 1 Eye Irrit. 2 Skin Sens. 1 STOT SE 3	 H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting eff 	
Aerosol 1 Eye Irrit. 2 Skin Sens. 1 STOT SE 3 Aquatic Chronic 3 • 2.2 Label elements • Labelling accordin	 H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting eff 	fects.

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S6 dunkelgrau



· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 $(Contd. \ on \ page \ 3)$

GB -

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S6 dunkelgrau

Dangerous components:		(Contd. of page
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<25%
CAS: 79-20-9 EINECS: 201-185-2	methyl acetate	5-<10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<5%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	1-<2.5%
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19-xxxx	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; \Leftrightarrow Skin Corr. 1B, H314; Eye Dam. 1, H318; \diamondsuit Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: $C \ge 0.001 \%$	≥0.001-<0.19

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

GB

[·] After eye contact:

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 3)

Trade name: Aerosol 1K Unifill S6 dunkelgrau

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

• Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

79-20-9 methyl acetate

WEL Short-term value: 770 mg/m³, 250 ppm Long-term value: 616 mg/m³, 200 ppm

(Contd. on page 5)

- GR -

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S6 dunkelgrau

50.02		(Contd. of page
78-93-3	3 butanone	
	Short-term value: 899 mg/m³, 300 ppm	
L	Long-term value: 600 mg/m³, 200 ppm	
S	Sk, BMGV	
110-82-	-7 cyclohexane	
WEL S	Short-term value: 1050 mg/m³, 300 ppm	
L	Long-term value: 350 mg/m³, 100 ppm	
108-65-	-6 2-methoxy-1-methylethyl acetate	
WEL S	Short-term value: 548 mg/m³, 100 ppm	
L	Long-term value: 274 mg/m ³ , 50 ppm	
S	Sk	
108-31-	-6 maleic anhydride	
WEL S	Short-term value: 3 mg/m ³	
L	Long-term value: 1 mg/m ³	
S	Sen	
Ingredi	ients with biological limit values:	
78-93-3	3 butanone	
BMGV	70 μmol/L	
	Medium: urine	
	Sampling time: post shift	
	Parameter: butan-2-one	
Additio	mal information: The lists valid during the making were used as basis.	

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

• Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

(Contd. on page 6)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 5)

• Eye/face protection Safety glasses

Tightly sealed goggles

*

SECTION 9: Physical and chemical prop	perties
9.1 Information on basic physical and chemical p	
General Information	roperues
Physical state	Aerosol
Colour:	According to product specification
Odour:	<i>Characteristic</i>
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	onuclermineu.
range	-24.9 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	2.6 Vol % (67-64-1 acetone)
Upper:	18.6 Vol % (115-10-6 dimethyl ether)
Flash point:	<0 °C
Ignition temperature:	455 °C (79-20-9 methyl acetate)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	ivoi uetermineu.
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	ivoi uetermineu.
water:	Not miscible or difficult to mix.
<i>Partition coefficient n-octanol/water (log value)</i>	Not determined.
Vapour pressure at 20 °C:	3,400 hPa (115-10-6 dimethyl ether)
Density and/or relative density	5,400 m a (115-10-0 amemyi emer)
Relative density	Not determined.
Vapour density	Not determined.
* · ·	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health an	d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	83.3 %
	With propellant gas. Content given by weight.
VOC (EU)	83.34 %
Solids content:	16.6 %
Change in condition	
Evaporation rate	Not applicable.

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S6 dunkelgrau

	(Contd. of page
Information with regard to physical hazard of	classes
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamme	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Ikke relevant.

(Contd. on page 8)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 7)

• 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

• Remark: Harmful to fish

 \cdot Additional ecological information:

• General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA UN1950 · 14.2 UN proper shipping name 1950 AEROSOLS · ADR · IMDG AEROSOLS · IATA AEROSOLS, flammable · 14.3 Transport hazard class(es) · ADR 2 5F Gases. · Class · Label 2.1 · IMDG, IATA 2.1 Gases. · Class · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void not classified · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): not classified (Contd. on page 9) GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

ude name: Aerosol 1K Unifill S6 dunko	elgrau
	(Contd. of p
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity litre: Category A. For AEROSOLS with a capacity a 1 litre: Category B. For WASTE AEROSOLS: Cate C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity litre:
	Segregation as for class 9. Stow "separated from" cla except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of cla For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of cla
· 14.7 Maritime transport in bulk acco	rding to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	lL
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
• Transport category	2
• Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities ($\widetilde{E}Q$)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

• Technical instructions (air):

Class	Share in %
NK	50-100

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- *H410 Very toxic to aquatic life with long lasting effects.*
- EUH018 In use may form flammable/explosive vapour-air mixture.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 : Aerosols – Category 3 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

 \cdot * Data compared to the previous version altered.