

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** Aerosol hitzebestaendig weiss 650°C

· **(Article number) product ID.:** REZ1223

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use SU21** Consumer uses: Private households / general public / consumers

· **Application of the substance / the mixture:** painting

· **Uses advised against** No further relevant information available.

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Peter Kwasny GmbH

Heilbronner Str. 96

D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20

E-mail: labor@kwasny.de

· **Further information obtainable from:** Product safety department

· **1.4 Emergency telephone number:** Tel.: +49 6269 95 20

· **national:**

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· **K-Nr.** 0001

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

**Trade name: Aerosol hitzbestaendig weiss 650°C**

(Contd. of page 1)

#### · 2.2 Label elements

##### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### · Hazard pictograms



GHS02    GHS07    GHS08

##### · Signal word *Danger*

##### · Hazard-determining components of labelling:

*xylene, mixture of isomers*

*acetone*

*n-butyl acetate*

*1-methoxy-2-propanol*

##### · Hazard statements

*H222 Extremely flammable aerosol.*

*H229 Pressurised container: May burst if heated.*

*H315 Causes skin irritation.*

*H319 Causes serious eye irritation.*

*H336 May cause drowsiness or dizziness.*

*H373 May cause damage to organs through prolonged or repeated exposure.*

##### · Precautionary statements

*P101 If medical advice is needed, have product container or label at hand.*

*P102 Keep out of reach of children.*

*P103 Read carefully and follow all instructions.*

*P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*

*P211 Do not spray on an open flame or other ignition source.*

*P251 Do not pierce or burn, even after use.*

*P260 Do not breathe vapours/spray.*

*P271 Use only outdoors or in a well-ventilated area.*

*P302+P352 IF ON SKIN: Wash with plenty of water.*

*P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*P312 Call a POISON CENTER/doctor if you feel unwell.*

*P332+P313 If skin irritation occurs: Get medical advice/attention.*

*P337+P313 If eye irritation persists: Get medical advice/attention.*

*P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*

*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

##### · Additional information:

*Without adequate ventilation, explosive atmosphere/gas mix may be created.*

*Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*

##### · Information concerning particular hazards for human and environment: 1272/2008/EC,II, 3.2

##### · 2.3 Other hazards

##### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

GB

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

**Trade name: Aerosol hitzebeständig weiss 650°C**

(Contd. of page 2)

### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10- <25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10- <25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	10- <25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10- <25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10- <25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5- <10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1- <2.5%
CAS: 12001-26-2	Mica substance with a Community workplace exposure limit	1- <2.5%
CAS: 67-56-1 EINECS: 200-659-6 Reg.nr.: 01-2119433307-44-xxxx	methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

Trade name: Aerosol hitzbestaendig weiss 650°C

(Contd. of page 3)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media** -
- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	--

(Contd. on page 5)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

**Trade name: Aerosol hitzbeständig weiss 650°C**

(Contd. of page 4)

**123-86-4 n-butyl acetate**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

**1330-20-7 xylene, mixture of isomers**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

**12001-26-2 Mica**

WEL Long-term value: 10\* 0.8\*\* mg/m<sup>3</sup>  
\*total inhalable \*\*respirable

**67-56-1 methanol**

WEL Short-term value: 333 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 266 mg/m<sup>3</sup>, 200 ppm  
Sk

**· Ingredients with biological limit values:****1330-20-7 xylene, mixture of isomers**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· **Hand protection**

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Nitrile rubber, NBR

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

Trade name: Aerosol hitzebeständig weiss 650°C

(Contd. of page 5)

- **Penetration time of glove material**

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

butyl rubber, 0,7mm

- **Eye/face protection**

Safety glasses



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Aerosol

- **Colour:**

According to product specification

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

-44 °C

- **Flammability**

Not applicable.

- **Lower and upper explosion limit**

- **Lower:**

1 Vol % (1330-20-7 xylene, mixture of isomers)

- **Upper:**

13 Vol % (67-64-1 acetone)

- **Flash point:**

<0 °C

- **Ignition temperature:**

365 °C (106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8)))

- **Decomposition temperature:**

Not determined.

- **pH**

Not determined.

- **Viscosity:**

- **Kinematic viscosity**

Not determined.

- **Dynamic:**

Not determined.

- **Solubility**

- **water:**

Not miscible or difficult to mix.

- **Partition coefficient n-octanol/water (log value)**

Not determined.

- **Vapour pressure at 20 °C:**

3,600 hPa (74-98-6 propane)

- **Density and/or relative density**

- **Relative density**

Not determined.

- **Vapour density**

Not determined.

- **9.2 Other information**

- **Appearance:**

- **Form:**

Aerosol

- **Important information on protection of health and environment, and on safety.**

- **Auto-ignition temperature:**

Product is not selfigniting.

- **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Not determined.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

Trade name: Aerosol hitzbestaendig weiss 650°C

(Contd. of page 6)

- **Solvent content:**
- **Organic solvents:** 71.4 %  
With propellant gas. Content given by weight.
- **VOC (EU)** 71.37 %
- **Solids content:** 26.4 %
- **Change in condition**
- **Evaporation rate** Not applicable.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Extremely flammable aerosol. Pressurised container:  
May burst if heated.
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

· <b>LD/LC50 values relevant for classification:</b>		
ATE (Acute Toxicity Estimates)		
Inhalative	LC50/4 h	2,678 mg/l

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

(Contd. on page 8)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

Trade name: Aerosol hitzbestaendig weiss 650°C

(Contd. of page 7)

## · 11.2 Information on other hazards

## · Endocrine disrupting properties

None of the ingredients is listed.

\* **SECTION 12: Ecological information**

## · 12.1 Toxicity

· **Aquatic toxicity:** No further relevant information available.· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.

## · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Ikke relevant.

## · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

## · 12.7 Other adverse effects

· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

\* **SECTION 13: Disposal considerations**

## · 13.1 Waste treatment methods

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.\* **SECTION 14: Transport information**

## · 14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1950

## · 14.2 UN proper shipping name

· **ADR** 1950 AEROSOLS· **IMDG** AEROSOLS· **IATA** AEROSOLS, flammable

## · 14.3 Transport hazard class(es)

· **ADR**· **Class** 2 5F Gases.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31


Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

Trade name: Aerosol hitzbestaendig weiss 650°C

(Contd. of page 8)

· <b>Label</b>	2.1
-----	
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	2.1 Gases.
· <b>Label</b>	2.1
-----	
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	Void not classified
-----	
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
-----	
· <b>14.6 Special precautions for user</b>	Warning: Gases.
· <b>Hazard identification number (Kemler code):</b>	- not classified
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
-----	
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
-----	
· <b>Transport/Additional information:</b>	
-----	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
-----	
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
VOC: <840g/l
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS

(Contd. on page 10)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

**Trade name: Aerosol hitzbestaendig weiss 650°C**

(Contd. of page 9)

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Technical instructions (air):**

Class	Share in %
I	<1
NK	50-100

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H370 Causes damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH018 In use may form flammable/explosive vapour-air mixture.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:** Product safety department

- **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- : Aerosols – Category 3
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 15.11.2022

Version number 1

Revision: 14.11.2022

**Trade name: Aerosol hitzbestaendig weiss 650°C**

(Contd. of page 10)

*STOT SE 1: Specific target organ toxicity (single exposure) – Category 1*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*  
*Asp. Tox. 1: Aspiration hazard – Category 1*  
**\* Data compared to the previous version altered.**

GB