


Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Page 1/10



Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss



· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 $(Contd. \ on \ page \ 3)$

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss

D		(Contd. of page
Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone	10-<25%
CAS: 79-20-9 EINECS: 201-185-2	methyl acetate	5-<10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone	2.5-<5%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate	1-<2.5%
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19-xxxx	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; \Leftrightarrow Skin Corr. 1B, H314; Eye Dam. 1, H318; \diamondsuit Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: $C \ge$ 0.001 %	<i>≥</i> 0.001-<0.19

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

GB

[·] After eye contact:

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 3)

Trade name: Aerosol 1K Unifill S1 weiss

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

• Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

- WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm
- 67-64-1 acetone
- WEL Short-term value: 3620 mg/m³, 1500 ppm
 - Long-term value: 1210 mg/m³, 500 ppm

79-20-9 methyl acetate

WEL Short-term value: 770 mg/m³, 250 ppm Long-term value: 616 mg/m³, 200 ppm

(Contd. on page 5)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss

78-93-	3 butanone (Contd. of p	age
	Short-term value: 899 mg/m ³ , 300 ppm	
	Long-term value: 600 mg/m ³ , 200 ppm	
	Sk, BMGV	
110-82	2-7 cyclohexane	
WEL S	Short-term value: 1050 mg/m³, 300 ppm	
	Long-term value: 350 mg/m ³ , 100 ppm	
108-65	5-6 2-methoxy-1-methylethyl acetate	
WEL S	Short-term value: 548 mg/m³, 100 ppm	
1	Long-term value: 274 mg/m ³ , 50 ppm	
S	Sk	
108-31	1-6 maleic anhydride	
WEL S	Short-term value: 3 mg/m ³	
	Long-term value: 1 mg/m ³	
S	Sen	
Ingred	lients with biological limit values:	
78-93	3 butanone	
BMGV	⁷ 70 μmol/L	
	Medium: urine	
	Sampling time: post shift	
	Parameter: butan-2-one	

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

• Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

(Contd. on page 6)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 5)

• Eye/face protection Safety glasses

Tightly sealed goggles

2

SECTION 9: Physical and chemical prop	perties
• 9.1 Information on basic physical and chemical p	properties
· General Information	-
· Physical state	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
• Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	-24.9 °C
Flammability	Not applicable.
• Lower and upper explosion limit	
· Lower:	2.6 Vol % (67-64-1 acetone)
Upper:	18.6 Vol % (115-10-6 dimethyl ether)
Flash point:	<0 °C
Decomposition temperature:	Not determined.
• pH	Not determined.
· Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
• water:	Not miscible or difficult to mix.
• Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3,400 hPa (115-10-6 dimethyl ether)
• Density and/or relative density	
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
· Important information on protection of health an	<i>id</i>
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	70.0.0
Organic solvents:	79.9 %
	With propellant gas. Content given by weight.
VOC (EU)	79.91 %
Solids content:	18.2 %
Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard class	
· Explosives	Void

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss

	(Contd. of page
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause drowsiness or dizziness.
- \cdot 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.

(Contd. on page 8)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss

(Contd. of page 7)

- · 12.7 Other adverse effects · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN number or ID number · ADR, IMDG, IATA UN1950 · 14.2 UN proper shipping name · ADR 1950 AEROSOLS · IMDG AEROSOLS · IATA AEROSOLS, flammable · 14.3 Transport hazard class(es) · ADR · Class 2 5F Gases. · Label 2.1 · IMDG, IATA 2.1 Gases. · Class · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void not classified · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): not classified · EMS Number: F-D, S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 (Contd. on page 9)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss

	(Contd. of page
	litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C. Cham of living supreme
· Segregation Code	C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of
Segregation Coue	litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
· 14.7 Maritime transport in bulk accor	ding to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

(Contd. on page 10)

⁻ GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol 1K Unifill S1 weiss

		(Contd. of page 9
H225	Highly flammable liquid and vapour.	(contait of page)
H226	Flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H315	Causes severe skin burns and eye damage. Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319		
	Causes serious eye irritation.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H336	May cause drowsiness or dizziness.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
	8 In use may form flammable/explosive vapour-air mixture.	
EUH066	6 Repeated exposure may cause skin dryness or cracking.	
Denartn	nent issuing SDS: Product safety department	
-	iations and acronyms:	
	cord relatif au transport international des marchandises dangereuses par route (European Agreemen	t Concerning th
	mal Carriage of Dangerous Goods by Road)	r concerning in
	nternational Maritime Code for Dangerous Goods	
IATA: Inte	ernational Air Transport Association	
	bally Harmonised System of Classification and Labelling of Chemicals	
	European Inventory of Existing Commercial Chemical Substances	
	European List of Notified Chemical Substances emical Abstracts Service (division of the American Chemical Society)	
	sistent, Bioaccumulative and Toxic	
	ry Persistent and very Bioaccumulative	
	s 1A: Flammable gases – Category 1A	
	: Aerosols – Category 1	
	s – Category 3	
	is (Comp.): Gases under pressure – Compressed gas 1. 2: Flammable liquids – Category 2	
	1. 2: Flammable liquids – Category 2 1. 3: Flammable liquids – Category 3	
	x. 4: Acute toxicity – Category 4	
	: 1B: Skin corrosion/irritation – Category 1B	
Skin Irrit.	2: Skin corrosion/irritation – Category 2	
	1: Serious eye damage/eye irritation – Category 1	
	2: Serious eye damage/eye irritation – Category 2	
	s. 1: Respiratory sensitisation – Category 1	
	. 1: Skin sensitisation – Category 1 . 1A: Skin sensitisation – Category 1A	
	3: Specific target organ toxicity (single exposure) – Category 3	
	1: Specific target organ toxicity (repeated exposure) – Category 1	
	1: Aspiration hazard – Category 1	
	cute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
	Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
1	Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	