

Page 1/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Lackstift AY Klarlack
- · (Article number) product ID.: REZ507
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Peter Kwasny GmbH

Heilbronner Str. 96

D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· **K-Nr.** 0001

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

· Signal word Warning

(Contd. on page 2)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Lackstift AY Klarlack

(Contd. of page 1)

#### · Hazard-determining components of labelling:

n-butyl acetate

#### · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

According to 1272/2008/EC I, 1.5.2, no identification on packing drums < 125ml with:

H226, P210, P280, P303+P361+P353

-----

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:	
CAS: 123-86-4	

EINECS: 204-658-1

🅸 Flam. Liq. 3, H226; ၺ STOT SE 3, H336, EUH066

50-100%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

n-butyl acetate

#### SECTION 4: First aid measures

· 4.1 Description of first aid measures

Reg.nr.: 01-2119485493-29-xxxx

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- $\cdot \textit{After skin contact:} \ \textit{Immediately wash with water and soap and rinse thoroughly}.$
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Lackstift AY Klarlack

(Contd. of page 2)

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of aerosols.

Take note of emission threshold.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Version number 1 Revision: 15.11.2022 Printing date 15.11.2022

Trade name: Lackstift AY Klarlack

(Contd. of page 3)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye/face protection



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

124-128 °C (123-86-4 n-butyl acetate) range Flammable.

· Flammability

· Lower and upper explosion limit

1.2 Vol % (123-86-4 n-butyl acetate) · Lower: · Upper: 7.5 Vol % (123-86-4 n-butyl acetate)

27 °C · Flash point: 370 °C · Ignition temperature: Not determined. · Decomposition temperature:  $\cdot pH$ 

Not determined.

(Contd. on page 5)

Version number 1 Revision: 15.11.2022 Printing date 15.11.2022

Trade name: Lackstift AY Klarlack

(Contd. of page 4)

· Viscosity:

· Kinematic viscosity Not determined. Not determined. · Dynamic:

·Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log value) Not determined.

10.7 hPa (123-86-4 n-butyl acetate) · Vapour pressure at 20 °C:

· Density and/or relative density

· Relative density Not determined. Not determined. · Vapour density

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Not determined.

· Solvent content:

· Organic solvents: 64.4 %  $\cdot$  VOC (EU) 64.33 % · Solids content: 35.7 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Void · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases · Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

#### SECTION 10: Stability and reactivity

- $\cdot \textbf{10.1 Reactivity} \ \textit{No further relevant information available}.$
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Lackstift AY Klarlack

· 10.6 Hazardous decomposition products: Possible in traces.

(Contd. of page 5)

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC30 values relevant for classification:				
123-86-4	n-butyl ace	tate		
Oral	LD50	13,100 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>21 mg/l (rat)		

- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

List II

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- $\cdot \textbf{12.4 Mobility in soil} \ \textit{No further relevant information available}.$
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Ikke relevant.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
$\cdot ADR$	1263 PAINT	
· IMDG, IATA	PAINT	

e /) --

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Lackstift AY Klarlack

(Contd. of page 6) · 14.3 Transport hazard class(es)  $\cdot ADR$ 3 (F1) Flammable liquids. · Class · Label · IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group III· ADR, IMDG, IATA not classified · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): not classified *F-E,S-E* · EMS Number: · Stowage Category A · 14.7 Maritime transport in bulk according to IMO instruments *Not applicable.* · Transport/Additional information: · Limited quantities (LQ) 5LCode: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category · Tunnel restriction code D/E  $\cdot$  *IMDG* · Limited quantities (LQ) 5L· Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT, 3, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 8)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Lackstift AY Klarlack

(Contd. of page 7)

- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- $\cdot \textit{Waterhazard class:} \textit{Water hazard class 1 (Self-assessment): slightly hazardous for water.} \\$
- $\cdot \textbf{15.2 Chemical safety assessment:} \ A \ Chemical \ Safety \ Assessment \ has \ not \ been \ carried \ out.$

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

## · Department issuing SDS: Product safety department

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* \* Data compared to the previous version altered.