

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** Aerosol NC Decklack uni mattiert, schwarz

· **(Article number) product ID.:** REZ1395

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use SU21** Consumer uses: Private households / general public / consumers

· **Application of the substance / the mixture:** painting

· **Uses advised against** No further relevant information available.

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Peter Kwasny GmbH

Heilbronner Str. 96

D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20

E-mail: labor@kwasny.de

· **Further information obtainable from:** Product safety department

· **1.4 Emergency telephone number:** Tel.: +49 6269 95 20

· **national:**

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· **K-Nr.** 0001

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol NC Decklack uni mattiert, schwarz

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07

· Signal word *Danger*

## · Hazard-determining components of labelling:

acetone  
n-butyl acetate  
butanone

## · Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

## · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.  
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.  
· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

## · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25- <50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10- <25%

(Contd. on page 3)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

**Trade name: Aerosol NC Decklack uni mattiert, schwarz**

(Contd. of page 2)

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing $\leq 0,1$ % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5- <10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	5- <10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5- <10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing $\leq 0,1$ % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5- <10%
CAS: 9004-70-0 Reg.nr.: no Reach No. available	nitrocellulose with water(not less than 25% water, by mass) ⚠ Expl. 1.1, H201	2.5- <5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5- <5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5- <5%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	1- <2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	1- <2.5%
CAS: 7397-62-8 EINECS: 230-991-7 Reg.nr.: 01-2119514685-36-xxxx	butyl glycollate ⚠ Repr. 2, H361; ⚠ Eye Dam. 1, H318	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

##### · 4.1 Description of first aid measures

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### SECTION 5: Firefighting measures

· **5.1 Extinguishing media -**

· **Suitable extinguishing agents:** Cool container with water

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

**Trade name: Aerosol NC Decklack uni mattiert, schwarz**

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

**67-64-1 acetone**

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

**123-86-4 n-butyl acetate**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

(Contd. on page 5)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol NC Decklack uni mattiert, schwarz

(Contd. of page 4)

**1330-20-7 xylene, mixture of isomers**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

**78-93-3 butanone**

WEL Short-term value: 899 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 600 mg/m<sup>3</sup>, 200 ppm  
Sk, BMGV

**64-17-5 ethanol**

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

**100-41-4 ethylbenzene**

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Sk

**· Ingredients with biological limit values:****1330-20-7 xylene, mixture of isomers**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

**78-93-3 butanone**

BMGV 70 µmol/L  
Medium: urine  
Sampling time: post shift  
Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

**· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

**· Respiratory protection:**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

**· Hand protection**

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

**Trade name: Aerosol NC Decklack uni mattiert, schwarz**

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material**

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

butyl rubber, 0,7mm

· **Eyeface protection**



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

1.7 Vol %

· **Upper:**

13 Vol %

· **Flash point:**

<0 °C

· **Ignition temperature:**

365 °C (106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8)))

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C:**

3,600 hPa

· **Density and/or relative density**

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**

· **Appearance:**

· **Form:**

Aerosol

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol NC Decklack uni mattiert, schwarz

(Contd. of page 6)

· **Important information on protection of health and environment, and on safety.**

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Not determined.

· **Solvent content:**· **Organic solvents:**

88.8 %

With propellant gas. Content given by weight.

· **Water:**

0.2 %

· **VOC (EU)**

88.78 %

· **Solids content:**

9.6 %

· **Change in condition**· **Evaporation rate**

Not applicable.

· **Information with regard to physical hazard classes**

· **Explosives**

Void

· **Flammable gases**

Void

· **Aerosols**Extremely flammable aerosol. Pressurised container:  
May burst if heated.· **Oxidising gases**

Void

· **Gases under pressure**

Void

· **Flammable liquids**

Void

· **Flammable solids**

Void

· **Self-reactive substances and mixtures**

Void

· **Pyrophoric liquids**

Void

· **Pyrophoric solids**

Void

· **Self-heating substances and mixtures**

Void

· **Substances and mixtures, which emit flammable gases in contact with water**

Void

· **Oxidising liquids**

Void

· **Oxidising solids**

Void

· **Organic peroxides**

Void

· **Corrosive to metals**

Void

· **Desensitised explosives**

Void

### SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.· **10.2 Chemical stability**· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **10.3 Possibility of hazardous reactions** No dangerous reactions known.· **10.4 Conditions to avoid** No further relevant information available.· **10.5 Incompatible materials:** No further relevant information available.· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**· **Acute toxicity**· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	686 mg/l
------------	----------	----------

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

**Trade name: Aerosol NC Decklack uni mattiert, schwarz**

(Contd. of page 7)

- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.


**SECTION 12: Ecological information**

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- |   |                     |
|---|---------------------|
| · <b>14.1 UN number or ID number</b>  |                     |
| · <b>ADR, IMDG, IATA</b>  | UN1950              |
| · <b>14.2 UN proper shipping name</b>   |                     |
| · <b>ADR</b>  | 1950 AEROSOLS       |
| · <b>IMDG</b>   | AEROSOLS            |
| · <b>IATA</b>   | AEROSOLS, flammable |
| · <b>14.3 Transport hazard class(es)</b>  |                     |
| · <b>ADR</b>  |                     |
|  |                     |
| · <b>Class</b>  | 2 5F Gases.         |

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31


Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol NC Decklack uni mattiert, schwarz

(Contd. of page 8)

· <b>Label</b>	2.1
-----	
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	2.1 Gases.
· <b>Label</b>	2.1
-----	
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	Void not classified
-----	
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
-----	
· <b>14.6 Special precautions for user</b>	Warning: Gases.
· <b>Hazard identification number (Kemler code):</b>	- not classified
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
-----	
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
-----	
· <b>Transport/Additional information:</b>	
-----	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
-----	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
-----	
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
VOC: <840g/l
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS

(Contd. on page 10)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

**Trade name: Aerosol NC Decklack uni mattiert, schwarz**

(Contd. of page 9)

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Technical instructions (air):**

Class	Share in %
Wasser	<1
NK	50-100

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH018 In use may form flammable/explosive vapour-air mixture.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** Product safety department

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Expl. 1.1: Explosives – Division 1.1
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- : Aerosols – Category 3
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 11)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

**Trade name: Aerosol NC Decklack uni mattiert, schwarz**

(Contd. of page 10)

*Repr. 2: Reproductive toxicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

**\* Data compared to the previous version altered.**

GB