

Page 1/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Aerosol Fill in fuer 2K Serie A · (Article number) product ID.: REZ81 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Application of the substance / the mixture: painting FOR PROFESSIONAL USE ONLY · Uses advised against Consumer uses: Private households / general public / consumers · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de · Further information obtainable from: Product safety department · 1.4 Emergency telephone number: Tel.:+49 6269 95 20 · national: National Poisons Information Service, Birmingham Tel.: 844 892 0111 · K-Nr. 0001

## **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.



Acute Tox. 4 H332 Harmful if inhaled.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A (Contd. of page 1) · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: Aliphatisches Polyisocyanat (HDI oligomers, isocyanurate) acetone n-butyl acetate · Hazard statements H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H332 Harmful if inhaled. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. P271 P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. *P337+P313* If eye irritation persists: Get medical advice/attention. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. *P410+P412* P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EUH204 Contains isocyanates. May produce an allergic reaction. · Information concerning particular hazards for human and environment: 1272/2008/EC,II, 3.2 · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

Printing date 15.11.2022

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A

CAS: 115-10-6	dimethyl ether	50-100%
EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
CAS: 67-64-1	acetone	10-<25%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
CAS: 28182-81-2	Aliphatisches Polyisocyanat (HDI oligomers, isocyanurate)	10-<25%
NLP: 500-060-2 Reg.nr.: 01-2119485796-17-xxxx	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	
CAS: 123-86-4	n-butyl acetate	2.5-<5%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	1-<2.5%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	🚸 Flam. Liq. 3, H226	

### **SECTION 4: First aid measures**

#### • 4.1 Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- *Wear protective equipment. Keep unprotected persons away.*
- $\cdot \textit{ 6.2 Environmental precautions: } Do not allow to enter sewers/ surface or ground water.$
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

(Contd. on page 4)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A

(Contd. of page 3)

• 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

# SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

## · Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

*Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.* 

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

### 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

#### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A

(Contd. of page 4)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

#### · Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material
- Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

 $\cdot$  For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

- · Eye/face protection
- Safety glasses



Tightly sealed goggles

<b>SECTION 9: Ph</b>	vsical and	l chemical	properties

Physical state	Aerosol	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point an	d boiling	
range	-24.9 °C	
Flammability	Not applicable.	
Lower and upper explosion limit		
Lower:	2.6 Vol % (67-64-1 acetone)	
Upper:	18.6 Vol % (115-10-6 dimethyl ether	
Flash point:	<0 °C	
Ignition temperature:	235 °C	
Decomposition temperature:	Not determined.	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic:	Not determined.	

(Contd. on page 6)

<sup>-</sup> GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A

	(Contd. of page
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3,400 hPa (115-10-6 dimethyl ether)
Density and/or relative density	
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health an	nd in the second s
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	88.2 %
	With propellant gas. Content given by weight.
VOC (EU)	88.17 %
Solids content:	11.8 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard classe	
Explosives	void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
Aerosois	
Oxidising gases	May burst if heated. Void
Gases under pressure	Void Void
Gases under pressure Flammable liquids	Void Void
Flammable solids	Void
	Void Void
Self-reactive substances and mixtures	Void Void
Pyrophoric liquids Pyrophoric solids	Void Void
	Void Void
Self-heating substances and mixtures	voiu
Substances and mixtures, which emit flammable	Void
gases in contact with water	Void Void
Oxidising liquids	
Oxidising solids	Void Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7) GB

<sup>· 10.2</sup> Chemical stability

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A

(Contd. of page 6)

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- $\cdot$  11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Harmful if inhaled.
- · LD/LC50 values relevant for classification:
- ATE (Acute Toxicity Estimates)
- Dermal LD50 16,914 mg/kg (rabbit)

Inhalative LC50/4 h 12.7 mg/l

- · Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- $\cdot$  11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- *Recommendation:* Disposal must be made according to official regulations.

SECTION 14: Transport information		
UN1950		
1950 AEROSOLS		
AEROSOLS		
	(Contd. on page 8	
	UN1950 1950 AEROSOLS	

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A (Contd. of page 7) · IATA AEROSOLS, flammable · 14.3 Transport hazard class(es) · ADR 2 5F Gases. · Class · Label 2.1 · IMDG, IATA 2.1 Gases. · Class 2.1 · Label · 14.4 Packing group · ADR, IMDG, IATA Void not classified · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): not classified · EMS Number: F-D, S-USW1 Protected from sources of heat. · Stowage Code SW2 Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. • Transport/Additional information: · ADR · Limited quantities (LQ) lLCode: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 · Tunnel restriction code D · IMDG · Limited quantities (LQ) lL• Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity (Contd. on page 9)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 8)

Trade name: Aerosol Fill in fuer 2K Serie A

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H312 Harmful in contact with skin.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- EUH018 In use may form flammable/explosive vapour-air mixture.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing SDS: Product safety department

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Fill in fuer 2K Serie A

(Contd. of page 9)

Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 : Aerosols – Category 3 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • \* Data compared to the previous version altered.